

# PureAir 8 Adsorbent Media



## Basic Information:

- PureAir 8 targets a broad range of gases that cause corrosion, odor, and other unwanted gases.
- PureAir Filtration starts with the highest grade activated alumina to ensure that the greatest possible adsorption capacity is reached. This alumina is then impregnated with potassium permanganate.
- PureAir Filtration adds a proprietary additive during the process in order to keep all eight percent of the permanganate available for reaction.

PureAir 8 has been developed to have roughly twice the capacity of PureAir 4. This media meets the requirements for UL certification.



General Description	Product Specifications	Removal Capability
<p>Spherical or cylindrical porous pellets formed from a combination of powdered activated alumina and other binders, suitably impregnated with potassium permanganate to provide optimum adsorption, absorption, and oxidation of a wide variety of gaseous contaminants.</p>	<ul style="list-style-type: none"> <li>• Particle Size: 4mm sphere</li> <li>• Density: 800 kg/m<sup>3</sup> (50 lbs/ft<sup>3</sup>)</li> <li>• Surface Area: 350 m<sup>2</sup>/g</li> <li>• Typical Moisture Content %: 20%</li> <li>• Crush Test: 40 lbs - 60 lbs</li> <li>• Abrasion Loss %: 3% max</li> <li>• Relative Pressure Drop: See Curve A*</li> <li>• Ignition Temperature: Non-ignitable</li> <li>• Permanganate Content: 8% minimum</li> </ul> <p>*See Curves Details at <a href="http://pureairfiltration.com/curves/">pureairfiltration.com/curves/</a></p>	<ul style="list-style-type: none"> <li>• Hydrogen Sulfide: 14% min by weight, or 0.112 grams per cc (per ASTM D6646-03)</li> <li>• Sulfur Dioxide: 7% by weight</li> <li>• Nitric Oxide: 5% by weight</li> <li>• Formaldehyde: 2.5% by weight</li> <li>• Nitric Dioxide: 20.96% by weight</li> </ul>

+1 678.935.1431

Toll Free: 866.543.7479

[www.PureAirFiltration.com](http://www.PureAirFiltration.com)

6050 Peachtree Pkwy, Suite 240-187, Atlanta, GA 30092 U.S.A.

