

Sulphasorb 2™ Adsorbent Media



Basic Information:

- PureAir Sulphasorb 2™ targets acidic gases, specifically hydrogen sulfide. This product has the same capacity by volume (0.15 g/cc) as original Sulphasorb™, but it has the upgraded benefit of fire resistance.
- PureAir starts with the highest grade activated carbon and activated alumina. The carbon and alumina are then impregnated with a caustic compound and a proprietary reagent to neutralize acidic gases.
- This product is designed to perform exceptionally well in both PureAir and other manufacturer's systems.



General Description	Product Specifications	Removal Capability*
<ul style="list-style-type: none"> • Porous, spherical or cylindrical pellets of high grade activated carbon • All varieties are UL compliant. 	<ul style="list-style-type: none"> • Particle Size: 4mm • Density: 690 kg/m³ (43 lbs/ft³) • Typical Moisture Content: 15% • Crush Test: 35 lbs - 70 lbs • Abrasion Loss: 4% max • Relative Pressure Drop: See Curve B* • CTC Value: 70% • Butane Activity: 27% minimum <p><small>*See Curves Details at pureairfiltration.com/curves/</small></p>	<ul style="list-style-type: none"> • Hydrogen Sulfide: 0.15 g/cc or approximately 26% by weight • Sulfur Dioxide: 10% by weight • Chlorine: 14% by weight <p><small>*same as original Sulphasorb™</small></p>

+1 678.935.1431

Toll Free: 866.543.7479

www.PureAirFiltration.com

6050 Peachtree Pkwy, Suite 240-187, Norcross, GA 30092

