

# CP Blend Adsorbent Media



## Basic Information:

CP Blend adsorbent media is a 50/50 percent blend of PureAir 4 potassium permanganate-based media and PureAir AC virgin bituminous activated carbon designed for the broadest range removal of corrosive, odorous, or toxic gases.

**Note: CP Blend media meets the requirements for UL certification.**



General Description	Product Specifications	Removal Capability
<p>CP Blend has the combined benefits of PureAir 4 and Activated Carbon.</p> <p><b>PureAir 4:</b> Spherical porous pellets formed from a combination of powdered activated alumina and other binders, suitably impregnated with potassium permanganate to provide optimum adsorption, absorption, and oxidation of a wide variety of gaseous contaminants.</p> <p><b>PureAir AC:</b> Porous, cylindrical pellets of high grade bituminous activated carbon.</p>	<ul style="list-style-type: none"> <li>• Particle Size: See base products</li> <li>• Density: 640 kg/m<sup>3</sup> (40 lbs/ft<sup>3</sup>)</li> <li>• Surface Area: See base products</li> <li>• Typical Moisture Content %: See base products</li> <li>• Crush Test: See base products</li> <li>• Abrasion Loss %: See base products</li> <li>• Relative Pressure Drop: See Curve B*</li> <li>• Permanganate Content: See base products</li> <li>• CTC Value: See base products</li> <li>• Iodine #: See base products</li> </ul> <p>*See Curves Details at <a href="http://pureairfiltration.com/curves/">pureairfiltration.com/curves/</a></p>	<ul style="list-style-type: none"> <li>• Hydrogen Sulfide: 4.0% by weight</li> <li>• Sulfur Dioxide: 4.7% by weight</li> <li>• Nitric Oxide: 2.8% by weight</li> <li>• Nitrogen Dioxide: 9.5% by weight</li> <li>• Formaldehyde: 1.4% by weight</li> </ul>

+1 678.935.1431

Toll Free: 866.543.7479

[www.PureAirFiltration.com](http://www.PureAirFiltration.com)

6050 Peachtree Pkwy, Suite 240-187, Atlanta, GA 30092 U.S.A.

