

SAFETY DATA SHEET

Version: 3.0 Date: April 2024

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878,

and United States Regulation 29 CFR 1910

	Section 1: Identification				
1.1	Product identifier Product Name	Sulphasorb XL			
	Product Code	SXL			
1.2	Relevant identified uses of the substance or mixture and uses advised against				
	Identified Use(s)	Gas-phase air filtration			
	Uses Advised Against	Do not use for applications other than those specified. It does not remove particulates or biological agents. Not for water Purification.			
1.3	Company Identification Details of the supplier of the safety data sheet	Pure Air Filtration, LLC 6050 Peachtree Parkway Suite 240-187 Atlanta, GA 30092 USA PureAir Filtration BV Tijnmuiden 79 1046 AK Amsterdam, The Netherlands			
	Telephone	+1 (678) 935-1431; Office Hours are Monday through Friday, 8:00AM to 5:00PM Eastern Standard Time			
	Fax	+1 (678) 935-0648			
	E-Mail	info@pureairfiltration.com			
1.4	Emergency telephone number	VelocityEHS 1-800-255-3924 (United States, Canada, Puerto Rico, U.S. Virgin Islands) +1-813-248-0585 (International, collect calls are accepted) 1-300-954-583 (Australia) 0-800-591-6042 (Brazil) 400-120-0751 (China) 000-800-100-4086 (India) 800-099-0731 (Mexico) The line is available 24 hours; in the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.			
	Language(s) spoken:	English			



Section 2: Hazard(s) Identification

2 1

Classification of the substance or mixture GHS-US and Regulation (EC) No. 1272/2008 (CLP) and most important hazards

This media is classified as not hazardous according to regulation (EC) 1272/2008 (CLP).

2.2

=:=	
Label Element: According to Regulation (EC) No. 1272/2008 (CLP)	
Product Name: Sulphasorb XL	
Contains:	Activated Carbon, Magnesium Oxide (proprietary mixture)

Hazard Pictograms(s)



Signal Word(s) Warning

Hazard Statements H315: skin irritation

H319 and H320: eye irritation

Precautionary Statements P264: Wash hands thoroughly after handling

P280: Wear protective gloves/protective clothing/eye P302+352: IF ON SKIN: wash with plenty of soap and water.

P332+313: IF SKIN irritation occurs: Get medical advice/attention.
P362: Take off contaminated clothing and wash before reuse

P401: Store in a cool, dry area in enclosed containers

P305+P351+P338- if in eyes, rinse with water for several minutes (after removing contact

lenses if present and easy to do without causing further irritation)

Supplemental Information

Other Hazards

Not applicable

If crushed or handled extensively, dust may evolve which can cause irritation to eyes and

respiratory tract. Adding water can cause irritation to skin.

2.3

Hazards not otherwise classified (HNOC) or not covered by GHS

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

If in a confined space, use appropriate safety precautions, as activated carbon can remove oxygen and cause hazard for workers in small space. Before entering space, check state and national guidelines for work in confined area.

The following medical conditions may be aggravated by exposure to the product: asthma, chronic lung disease, and skin rashes.

Section 3: Composition/Information on Ingredients

Chemical Name	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Statement(s)
Activated Carbon	Up to 90%	7440-44-0	231-153-3	01-2119488716-22-XXXX	Not Classified
Magnesium Oxide	Up to 25%	1309-48-4	215-171-9	This product is Exempt from REACH registration requirements	Eye Irr. 2; H319+H320



Section 4: First-Aid Measures

4.1

Description of first aid measures

Self-protection of the first aider: Use personal protective equipment as required. Wear suitable protective clothing and gloves. Avoid contact with skin, eyes, or clothing. Do not breathe dust. Do not ingest. Take off contaminated clothing and wash before reuse.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Gently wash with plenty of soap and water. Call a doctor and/or poison control center.

IF IN EYES: Flush eyes with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. After rinsing affected eyes must be seen by an ophthalmologist. Call doctor and/or poison control center.

IF INHALED: If breathing is difficult, move to fresh air and keep at rest in a position comfortable for breathing. Immediately call a doctor and/or poison control center.

IF SWALLOWED: Do NOT induce vomiting. Do not give anything by mouth to an unconscious person. Immediately call a doctor and poison control center.

4.2

Most important symptoms and effects, both acute and delayed

See Section 11 for additional Toxicological information.

4.3

Indication of any immediate medical attention and special treatment needed

Notes to a physician: Product is expected to be non-toxic and only an eye irritant in the powder form. Treat symptomatically. IF IN EYES: Obtain prompt consultation, preferably from an ophthalmologist.

Section 5: Fire-Fighting Measures

5.1

Suitable extinguishing media

If possible, to do so safely, move smoldering activated carbon to a non-hazardous area, preferably outdoors. As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical, foam, or water spray. Alcohol resistant foams (ATC type) are preferred.

Unsuitable extinguishing media

Do not use water jets. Direct water jets may spread the fire.

Wet activated carbon depletes oxygen from the air. Materials allowed to smolder for long periods in enclosed spaces may produce amounts of carbon monoxide, which may reach the lower explosive limit for carbon monoxide of 12.5% in air.

5.2

Special protective equipment for firefighters

Fight fire with normal precautions from a reasonable distance. Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Keep containers cool by spraying with water if exposed to fire.

5.3

Special Hazards arising from the substance or mixture

May form explosive dust/air mixtures. May decompose if heated. Burning produces irritant fumes. Not flammable but will support combustion.

Activated carbons have a high surface area which may cause self-heating during oxidation. Activated carbon is difficult to ignite and tends to burn slowly (smolder) without producing smoke or flame.

Materials allowed to smolder for long periods in enclosed spaces may produce amounts of carbon monoxide, which may reach the lower explosive limit for carbon monoxide of 12.5% in air.



Section 6: Accidental Release Measures

6.1

Personal precautions, Protective Equipment, and Emergency Procedures

Ensure operatives are trained to minimize exposure. Ensure suitable personal protection during removal of spillages. Use personal protective equipment as required. See Section 8. Wear suitable protective clothing, gloves and eye/face protection. Avoid all contact. Avoid dust formation. Take off contaminated clothing and wash before reuse. Ensure adequate ventilation. Do not breathe dust. Do not ingest. If swallowed, then seek immediate medical assistance. In case of leakage, eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking.

6.2

Environmental precautions

Collect spillage. Inform authorities if spill cannot be contained.

6.3

Methods and material for containment and cleaning up

Small Spillages: Sweep up spilled substances and remove to safe place. Avoid dust generation.

Clean up using dry procedures (broom, shovel, etc.); avoid dusting.

Do not mix with combustible material. Clean up using dry procedures (broom, shovel, etc.); avoid dusting. Product may be recovered for use if it has not come in contact with liquid, or been exposed to significant amounts of gaseous contaminants. Transfer to a container for disposal. If the spilled carbon contains dust or has the potential to create dust, use explosion-proof vacuums and/or cleaning systems suitable for combustible dusts.

Dispose of unused material in a facility permitted for non-hazardous wastes. Spend (used) carbon should be disposed of in accordance with applicable laws.

6.4

Reference to other sections

See also Section 8, 13

Section 7: Handling and Storage

7.1

Precautions for safe handling

Ensure operators are trained to minimize exposures. Use personal protective equipment as required. **See Section 8**. Wear suitable protective clothing, gloves, and eye/face protection. Avoid all contact. Ensure adequate ventilation. In case of inadequate ventilation wear respiratory protection. Do not eat, drink, or smoke when using this product. Wash hands before breaks and after work. Use air conveying (vacuum) for bulk removal. If manual handling is used for transfer (from vessel, sling bags, boxes, or pails), use mechanical ventilation or other measures to remove airborne dust.

Confined space entry: appropriate safety precautions should be taken when entering any confined space. Entering containers or media vessels/tanks housing active carbon for may remove oxygen from the air causing severe hazards for workers entering such spaces. Prior to entering a confined space that contains or previously contained activated carbon, the space should be evaluated for oxygen and carbon monoxide concentrations, and any other hazard, by a qualified person. All local, state, and federal regulations should be followed. Avoid crushing the product to keep dusting to a minimum. As described under Handling above, mechanical ventilation or other measures may be needed to remove airborne dust. Protect from water exposure to contaminated air (gaseous, particulate, and aerosol contaminated), otherwise the product may be rendered useless.

7.2

Conditions for safe storage, including any incompatibilities.

Do not store near combustible materials. Do not mix with combustible material. Activated carbon has a high surface area which may cause self-heating during oxidation. Take precautionary measures against static discharge. All metal parts of the processing equipment must be grounded.

Not an oxidizer but contact with strong oxidizers could intensity fire.

Keep container tightly closed. Store in a cool/low-temperature, well-ventilated (dry) place away from heat and ignition sources. Control dust formation. No smoking. Do not store together with strong oxidizing agents. Prior to entering a confined space that contains or previously contained activated carbon, the space should be evaluated for oxygen and carbon monoxide concentrations, and any other hazard, by a qualified person.

Control dust formation. Recommended to package in plastic-lined corrugated boxes, or in bulk sacks. Do not package in a porous material that allows contact to air, water, and contaminants.



Storage Temperature

Keep only in the original container/package in a cool well-ventilated place away from heat and ignition sources. Should be stored inside, away from rainwater, etc.

Incompatible materials

Protect from moisture. Keep away from strong oxidizing substances and combustible materials. Not an oxidizer but contact with strong oxidizers could intensity fire. Product should be kept protected from water and exposure to contaminated air (gaseous, Particulate, and aerosol contaminated), otherwise the product may be rendered useless.

Specific end use(s)

See Section 1.2.

Section 8: Exposure Controls / Personal Protection

8.1

Control Parameters Related to Substance - Carbon

OSHA PEL (TWA) (15 mg/m³ total dust; 5 mg/m³ respirable fraction)

Occupational Exposure Limits

Dust, or Particulates, Substance Not Otherwise Specified:

Austria MAK: 10 mg/m³, STEL 2x30 min, Inhalable dust; 5 mg/m³, TWA, Inhalable dust

Belgium: 10 mg/m³, TWA Inhalable; 3 mg/m³, TWA Respirable

Canada (Saskatchewan): 10 mg/m³, TWA Inhalable; 3 mg/m³, TWA, Respirable

China: 8 mg/m³, TWA; 10 mg/m³, STEL

France: 10 mg/m3 TWA Inhalable dust; 5 mg/m3, TWA Respirable dust

Germany - TRGS 900: 10 mg/m³, TWA, Inhalable; 3 mg/m³, Respirable fraction

Hong Kong: 10 mg/m³, TWA

Ireland PELs: 10 mg/m³, TWA Total inhalable; 4 mg/m³, TWA Respirable

Italy: 10 mg/m³, TWA Inhalable; 3 mg/m³, TWA Respirable

Japan: 3 mg/m³ TWA Respirable

Malaysia: 10 mg/m³, TWA Inhalable; 3 mg/m³, TWA Respirable The Netherlands: 3.5 mg/m³, Inhalable

Spain: 10 mg/m³, VLA, Inhalable; 3 mg/m³, VLA, Respirable

Sweden: 10 mg/m³, NGV, Total inhalable; 5 mg/m³, NGV, Respirable

United Kingdom - WEL: 10 mg/m³, TWA, Total Inhalable dust; 4 mg/m³, TWA, Respirable dust

US ACGIH - PNOS: 10 mg/m³, TWA Inhalable; 3 mg/m³, TWA Respirable US OSHA - PEL: 15 mg/m³, TWA Total dust; 5 mg/m³, TWA Respirable

Biological Limit Value:

None Known

PNECs and DNELs

Not Applicable

8.2

Exposure Controls

Appropriate Engineering Controls

Ensure operators are trained to minimize exposures. Ensure adequate ventilation. In case of inadequate ventilation wear respiratory protection. Good hygiene practices and housekeeping measures. A washing facility/water for eye and skin cleaning purposes should be present. Preferably use engineering controls to keep exposures below the OEL or DNEL. Minimize eye and skin contact by using appropriate protective equipment. Use local or general room ventilations to control airborne dust that may be generated.

Environmental Exposure Controls

Prevent release to the environment.

Personal Protection Equipment (PPE)

Use personal protective equipment as required. Wear suitable protective clothing, gloves, and eye/face protection. Keep good industrial hygiene. Do not breathe dust. Avoid all contact. Wash hands before breaks and after work. Keep work clothes separately. Take off contaminated clothing and wash before reuse. Do not eat, drink, or smoke at the workplace. Protective clothing should be selected specifically for the working place, depending on the concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier.



Eye / Face Protection	Hand & Skin Protection	Respiratory Protection
Use eye protection according to EN 166, designed to protect against dust.	Wear gloves to EN374 to protect against skin effects from powders.	Respiratory protective devices may be necessary if local exhaust ventilation is not adequate.
For Small Quantities: Not Normally Required	Wear suitable coveralls to prevent exposure to the skin.	

Section 9: Physical and Chemical Properties

9.1

Basic physical and chemical properties

Physical state: Solid cylindrical pellets

Color: Black
Odor: No Odor
Melting point/melting range: N/A
Boiling point/boiling range: N/A

Flammability: Not flammable Lower and upper explosion limits: Not explosive.

Flash point:

Auto ignition temperature:

N/A

Decomposition temperature:

N/A

N/A

N/A

PH:

6.9-9.0

Viscosity:

N/A

Solubility: Partially soluble in water

Partition coefficient n-octanol/water (log value): N/A Vapor pressure: N/A

Density and/or Relative density: 400-480 kg/m³

Relative vapor density: N/A

Particle Characteristics: Median Particle Diameter 4mm

9.2

Other Information

Oxidizing Properties: N/A

Section 10: Stability and Reactivity

10.1

Reactivity

Stable under normal conditions.

10.2

Chemical stability

Stable under normal conditions

10.3

Possibility of hazardous reactions

None under normal processing. Involvement in fire may release carbon monoxide and dioxide.

10.4

Conditions to avoid

Dust formation. Eliminate sources of ignition. Protect from moisture, damage, heat, and sunlight. Keep in airtight container, as contaminated air can render product useless.

10.5

Incompatible materials

Strong oxidizing agents such as ozone, liquid oxygen, chlorine, permanganate.



10.6

Hazardous decomposition products

Materials allowed to smolder for long periods in enclosed spaces may produce amounts of carbon monoxide which reach the lower explosive limit (LEL = 12.5% in air). Used activated carbon may produce additional combustion products which are based on the substance(s) adsorbed, carbon oxides.

Section 11: Toxicological Information

11.1

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - Ingestion: Based on available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: LD50 > 10000 mg/kg bw/day

Acute toxicity – Inhalation: Based on available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: LC50 > 100 ml/l

Acute toxicity – Skin contact: Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Skin. Irr.2- H315: causes skin irritation

Serious eye damage/irritation: Eye. Irr.2 – H319 and H320: causes serious eye irritation.

Respiratory or skin sensitization: Not classified

Germ cell mutagenicity:
Carcinogenicity:
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.

Aspiration hazard: Not relevant -solid mixture

11.2

Information on other hazards

Endocrine disrupting properties: No substances identified as having endocrine-disrupting properties. **Other information:** No data available.

Section 12: Ecological Information

12.1

Toxicity: No data available. No known toxicity concerns.

12.2

Persistence and degradability: No data available.

12.3

Bioaccumulation: Not expected due to physicochemical properties of the substance.

12.4

Mobility in soil: No data available.

12.5

Results of PBT and vPvB Assessment: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6

Endocrine Disrupting Properties: No substances identified as having endocrine-disrupting properties.

12.7

Other Adverse Effects

None Known.



Section 13: Disposal Considerations

13.1

Waste Disposal Methods

Unused material is not a hazardous material or hazardous waste. Dispose of waste in an approved waste disposal facility, according to local laws.

Spent (used) activated carbon may be classified as a non-hazardous or hazardous waste depending upon its use, the substance(s) adsorbed, and how it is ultimately managed. Follow applicable regulations for disposal.

Section 14: Transport Information

14.1

Transportation Information

	ADR/RID/DOT	IMDG	IATA/ICAO
UN Number or ID Number	None	None	None
UN Proper Shipping Name	Activated Carbon	Activated Carbon	Activated Carbon
Transport Hazard Class(es)	None	None	None
Packing Group	None	None	None
Environmental Hazards	No	No	No
Special Precautions for User	None known	None known	None known

14 2

Maritime transport in bulk according to IMO instruments

The media contains more than 50% activated carbon, which is produced by a steam activation process. Because of this the media is not subject to the provisions of the International Dangerous Goods Code (IMGD) or the labeling and packaging requirements of the International Maritime Organization (IMO) Class 4.2.

14.3

Additional information: NMFC 40560 Activated Carbon, Purifying

Section 15: Regulatory Information

15.1

Safety, health, and environmental regulations/legislation specific for the substance or mixture

National Regulations

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs): No

TSCA (Toxic Substances Control Act): No

EU Regulations

Not restricted for the intended use(s) of the product. Just note for classifications and labelling that it is an Xi-irritant.

CoRAP Substance Evaluation

N/A

Other National Regulations

Other Not Known. California Proposition 65 – Product does not contain known substances to cause cancer or reproductive harm.

15.2

Chemical Safety Assessment

A chemical safety assessment is not required under REACH.



Section 16: Other Information

The following sections contain revisions or new statements: Updated substance / mixture classification. New SDS Regulation 2020/878 format, all sections have been updated to include new information. Please review SDS with care.

References: Existing Safety Data Sheet (SDS) Substance with harmonized classification and labelling according to Regulation (EC) No. 1272/2008, Annex VI.

EU Classification: This Safety Data Sheet was prepared in accordance with EC Regulation (EC) 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

16.1

Full list of H Statements

Skin Irrit. 2; Skin irritant, Category 2

H315: Causes skin irritation.

Eye Irrit. 2; Eye irritant, Category 2

H319: Causes serious eye irritation.

H320: Causes eye irritation.

16.2

LEGEND for acronyms used in this SDS / MSDS

ADR ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road CLP

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

CORAP Community Rolling Action Plan (CoRAP)

DNEL Derived no effect level

EC50 Half maximal effective concentration

IATA IATA: International Air Transport Association
ICAO ICAO: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods

LC50 Lethal concentration at which 50% of the population is killed

LD50 Lethal dose at which 50% of the population is killed

LTEL Long term exposure limit
OEL Occupational exposure limits

PBT: Persistent, Bio accumulative and Toxic

PNEC Predicted No Effect Concentration

REACH Registration, Evaluation, Authorization and Restriction of Chemicals

RID Regulations concerning the international railway transport of dangerous goods STEL Short term exposure

limit

vPvB: very Persistent and very Bioaccumulative.

Training advice:

Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to users is believed to be accurate and is given in good faith, but it is for the users to satisfy themselves of the suitability of the product for their own particular purpose. Pure Air Filtration, LLC. Gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Pure Air Filtration accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright, and Designs cannot be assumed.